

Your Direct Source for Rackmount Solutions



EJ-5U6528

Dimensions:

19"(W) x 8.7"(H) x 25.6"(D)

Drive Bays:

1x slim CDROM, 1x slim FDD,
24x hotswap drive carrier,
2x 3.5" internal



Rackmount 1U~6U & Wallmount Openrack & Cabinet

- 1U~6U Server Chassis/Data Storage Server Chassis & Wallmount
- Main frames Cabinet w/door, Easy assembly Open Rack

RACKMOUNTS - 1U

Model	Depth (in.)	Motherboard Size	Fans Incl.	Optional Fans	Ext Bays	Int Bays	Hot-Swap Trays	Power Supply
EJ-1U222-C	8.66	Mini-ITX (Max 6.7" x 6.7")	none	none	slim CD	1 x 3.5"	none	P1U 150W Installed
EJ-1U403-C	16.02	ATX (Max 12" x 9.6")	3 x 40mm	none	slim CD, slim FDD	1 x 3.5"	none	P1U
EJ-1U523-C	20.50	ATX (Max 12" x 9.6")	2 x 40mm	none	2 x 5.25", 1 x 3.5"	2 x 2.5"	none	P1U
EJ-1U236-C	23.62	ATX, Micro ATX, Mini ATX	5x40mm (mid & rr)	none	1 x 5.25", 1 x 3.5"	2 x 3.5"	none	P1U
EJ-1U2510-C	25.60	ATX (Max 12" x 13")	6 x 40mm	none	slim CD	1 x 2.5"	8 x 2.5" U320 carrier	P1U
EJ-1U643-C	25.60	ATX (Max 12" x 13")	7 x 40mm	none	1 x 5.25"	none	2 x 3.5"	P1U
EJ-1U653-C	25.60	ATX (Max 12" x 13")	6 x 40mm	none	1 x 5.25"	none	2 x 3.5"	P1U
EJ-1U656-C	25.60	ATX (Max 12" x 13")	6 x 40mm	none	slim CD, slim FDD	none	4 x 3.5"	P1U

RACKMOUNTS - 2U

Model	Depth (in.)	Motherboard Size	Fans Incl.	Optional Fans	Ext Bays	Int Bays	Hot-Swap Trays	Power Supply
EJ-2U354-C	13.9	ATX (Max 12" x 9.6")	1 x 80mm, 2 x 40mm	none	1 x 5.25"	3 x 3.5"	none	P1U 250W Installed
EJ-2U455-C	17.7	ATX (Max 12" x 9.6")	3 x 80mm	none	1 x 5.25", 1 x 3.5"	3 x 3.5"	none	P2U
EJ-212-C	19.7	ATX 12" x 9.6"	1 x 8cm, 1 x 6cm	none	1 x 5.25", 1 x 3.5"	3 x 3.5"	none	PS2 (remote cable needed)
EJ-2U657-C	23.6	ATX (Max 12" x 13")	3 x 8cm	none	2 x 5.25", 2 x 3.5"	3 x 3.5"	none	P2U
EJ-268-C	24.4	ATX, Micro ATX (Max 12" x 13")	2 x 8cm	4 x 8cm	2 x 5.25", 2 x 3.5"	2 x 3.5"	none	P2U
EJ-232-C	25.6	ATX (Max 12" x 13")	3 x 8cm, 1 x 6cm	none	1 x 5.25", 1 x 3.5"	5 x 3.5"	none	PS2
EJ-2U256-C	25.6	ATX (Max 12" x 13")	1 x 60mm, 1 x 80mm	none	1 x 5.25", 1 x 3.5"	3 x 3.5"	none	PS2
EJ-2U655-C	25.6	ATX (Max 12" x 13")	3 x 80cm	none	1 x 5.25"	none	5 x 3.5"	P2U
EJ-270-C	26.5	ATX (Max 12" x 13")	2 x 8cm, 1 x 4cm	3 x 4cm	1 x 5.25", 1 x 3.5", slim CD	none	6 x 3.5"	P2U / Redundant
EJ-2U6510-C	32.5	ATX (Max 12" x 13")	4 x 8cm	none	slim CD, slim FDD, 1 x 3.5"	2 x 2.5"	8 x 3.5"	P2U

RACKMOUNTS - 3U

Model	Depth (in.)	Motherboard Size	Fans Incl.	Optional Fans	Ext Bays	Int Bays	Hot-Swap Trays	Power Supply
EJ-3U404-C	15.7	ATX (Max 12" x 9.6")	2 x 80mm, 1 x 60mm	none	1 x 5.25", 1 x 3.5"	2 x 3.5"	none	P2U Redundant
EJ-3U528-C	20.7	ATX (Max 12" x 9.6")	2 x 90mm, 1 x 80mm	none	2 x 5.25", 1 x 3.5"	5 x 3.5"	none	PS2 (remote cable needed)
EJ-3U6510-C	25.6	ATX (Max 12" x 13")	3 x 9cm	2 x 4cm	2 x 5.25", 1 x 3.5"	9 x 3.5"	none	P2U Redundant
EJ-3U6513-C	25.6	ATX (Max 12" x 13")	4 x 9cm, 1 x 6cm	none	1 x 5.25", slim CD, slim FDD	2 x 3.5" (optional)	10 x 3.5"	P2U Redundant
EJ-3U6514-C	25.6	ATX (Max 12" x 13")	4 x 90mm, 1 x 60mm	none	slim CD, slim FDD	2 x 2.5"	12 x 3.5"	P2U Redundant
EJ-3U6517-C	25.6	ATX (Max 12" x 13")	4 x 92mm, 1 x 60mm	none	slim CD	none	16 x 3.5"	P2U Redundant
EJ-3U659-C	25.6	ATX (Max 12" x 13")	4 x 90mm, 2 x 40mm	none	2 x 5.25", 2 x 3.5"	1 x 3.5"	4 x 3.5"	P2U Redundant

RACKMOUNTS - 4U

Model	Depth (in.)	Motherboard Size	Fans Incl.	Optional Fans	Ext Bays	Int Bays	Hot-Swap Trays	Power Supply
EJ-4U454-C	17.8	ATX (Max 12" x 9.6")	1 x 12cm	1 x 12cm	3 x 5.25", 1 x 3.5"	none	none	PS2 / Mini-Redundant
EJ-4U489-C	18	ATX (Max 12" x 9.6")	1 x 120mm, 1 x 80mm	none	3 x 5.25", 1 x 3.5"	5 x 3.5"	none	PS2
EJ-4U509-C	19.7	ATX (Max 12" x 13")	2 x 9cm, 3 x 9cm	none	10 x 5.25"	none	none	PS2 / Mini-Redundant
EJ-4U418-C	20.1	ATX (Max 12" x 9.6")	1 x 12cm	none	3 x 5.25", 1 x 3.5"	2 x 3.5"	none	PS2 / Mini-Redundant
EJ-4U515-C	20.1	ATX (Max 12" x 9.6")	1 x 12cm	none	3 x 5.25", 1 x 3.5"	1 x 3.5"	none	PS2 / Mini-Redundant
EJ-4U519-C	20.1	ATX (Max 12" x 13")	2 x 90mm, 2 x 60mm	none	2 x 5.25", 1 x 3.5"	6 x 3.5"	none	PS2 / Mini-Redundant
EJ-4U5713-C	22.5	ATX (Max 12" x 9.6")	3 x 12cm, 2 x 6cm	none	8 x 5.25", 1 x 3.5"	4 x 3.5"	none	PS2 / Redundant
EJ-4U6210-C	24.5	ATX (Max 12" x 13")	3 x 120mm	2 x 60mm	10 x 5.25"	none	none	PS2 / Mini-Redundant
EJ-4U6213-C	24.5	ATX (Max 12" x 9.6")	3 x 12cm, 2 x 6cm	none	8 x 5.25", 1 x 3.5"	4 x 3.5"	none	PS2 / Redundant
EJ-4U6517-C	25.6	ATX (Max 12" x 13")	4 x 90mm, 1 x 60mm	none	1 x 5.25", slim CD, slim FDD	none	14 x 3.5"	PS2 / Redundant
EJ-4U6518-C	25.6	ATX (Max 12" x 13")	4 x 90mm, 1 x 60mm	none	slim CD, slim FDD	2 x 2.5", 2 x 3.5" (opt)	16 x 3.5"	PS2 / Redundant
EJ-4U676-C	26.4	ATX (Max 12" x 13")	Hot Swap 4 x 9cm	3 x 12cm	3 x 5.25", 1 x 3.5"	2 x 3.5", 2 x 3.5" (opt)	none	PS2 / Mini-Redundant
EJ-4U678-C	26.4	ATX (Max 12" x 13")	Hot Swap 4 x 9cm	none	6 x 5.25", 1 x 3.5"	2 x 3.5" (optional)	none	PS2 / Mini-Redundant

RACKMOUNTS - 5U / 6U / WALLMOUNT

Model	Depth (in.)	Motherboard Size	Fans Incl.	Optional Fans	Ext Bays	Int Bays	Hot-Swap Trays	Power Supply
EJ-580-C (Multilane) **	25.6	ATX (Max 12" x 13")	3 x 12cm, 1 x 8cm, 2 x 6cm	none	slim CD, slim FDD	2 x 3.5", 2 x 2.5"	24 x 3.5"	PS2 / Mini-Redundant
EJ-5U6528-C	25.6	ATX (Max 12" x 9.6")	3 x 40mm	none	slim CD, slim FDD	2 x 3.5"	24 x 3.5"	1350W RPS Installed
EJ-5U6528-C (Multilane)**	25.6	ATX (Max 12" x 9.6")	3 x 40mm	none	slim CD, slim FDD	2 x 3.5"	24 x 3.5"	1500W RPS Installed
EJ-6U6638-C (Multilane)**	26.2	EATX (Max 13" x 16")	2 x 120mm, 5 x 60mm	none	2 x 5.25" (optional)	2 x 3.5"	36 x 3.5", 4 x 3.5" (opt)	1500W RPS Installed
EJ-530-C	26.4	ATX (Max 12" x 13")	Hot Swap 4 x 9cm	3 x 12cm	4 x 5.25", 1 x 3.5"	none	none	Redundant
EJ-060-C	Wallmount	Micro ATX (Max 9.6" x 9.6")	1 x 9cm	none	1 x 5.25", 1 x 3.5"	2 x 3.5"	none	PS2 / Mini-Redundant
EJ-061-C	Wallmount	Micro ATX (Max 9.6" x 9.6")	1 x 9cm	none	1 x 5.25", 1 x 3.5"	1 x 3.5"	none	P1U / Flex ATX
EJ-080 -C	Wallmount	Micro ATX (Max 9.6" x 9.6")	1 x 12cm	none	2 x 5.25", 1 x 3.5"	1 x 3.5"	none	PS2 / Mini-Redundant
EJ-120-C	Wallmount	Flex or Micro ATX (Max 9.6" x 9.6")	1 x 12cm	none	2 x 5.25", 2 x 3.5"	1 x 3.5"	none	PS2 / Mini-Redundant
EJ-B08-C	Wallmount	Micro ATX (Max 9.6" x 9.6")	Hot Swap 2 x 90mm	none	1 x 5.25", 1 x 3.5"	1 x 3.5"	none	PS2 / Mini-Redundant

** Multilane Data Cables Not Included

* Hot-Swap Drive Trays Interface: IDE, SATA, SCSI 320, SAS



Corporate Headquarters
 230 Paseo Sonrisa Walnut, California 91789 USA
 Toll Free (888) 696-DYNA Toll Free (888) 696-3962
 Fax Number (909) 598-3465

NJ Distribution Center
 400 Appgar Dr. Unit D Somerset, New Jersey 08873 USA
 Website: <http://www.dynapowerusa.com>
 E-mails: Sales: dp_sales@dynapowerusa.com